

DVX506 AT

5.0 Ton Diesel Forklift
with Automatic Transmission

CEV - V



Why Buy Me?

- ✓ Maximum Reliability
- ✓ Maximum Performance
- ✓ Maximum Productivity


Attachments



DVX506 AT - SPECIFICATIONS



Characteristics	1.1	Manufacturer	-	KION India
	1.2	Model Designation	-	DVX506 AT
	1.3	Power Unit: Battery/Diesel	-	Diesel
Weight	1.4	Operation: Manual, Stan-On, Seated	-	Seated
	1.5	Load Capacity	Q(kg)	5000
	1.6	Load Center	C(mm)	600
Wheels & Tyres	1.7	Axle Center to Fork Face	X(mm)	510
	1.8	Wheelbase	Y(mm)	2200
	2.1	Service Weight - Laden/Unladen	kg	6920*
Dimensions	2.2	Axle Load Laden, Front/Rear	kg	10680/1280
	2.3	Axle Load Unladen, Front/Rear	kg	3270 /3690
	3.1	Tyre: Solid, Pneumatic, Superelastic	-	Solid
Performance	3.2	Tyre: Size, Front	-	7.00-12
	3.3	Tyre: Size, Rear	-	7.00-12
	3.4	Wheels, Number Front/Rear (x=drive)	-	4/2
Others	3.5	Track Width, Front	b10 mm	1400
	3.6	Track Width, Rear	b11 mm	1280
	4.1	Mast Tilt, Forward/Backward	a/?	Refer Table*
Drive	4.2	Mast Height, Lowered	h1 mm	Refer Table*
	4.3	Freelift	h2 mm	Refer Table*
	4.4	Maximum Fork Height	h3 mm	Refer Table*
Performance	4.5	Mast Height, Extended	h4 mm	Refer Table*
	4.6	Height of Overhead Guard	h6 mm	Refer Table*
	4.7	Seat Height	h7 mm	1260
Others	4.8	Towing Coupling Height	h10 mm	350
	4.9	Overall Length	L1 mm	4510
	4.10	Length to Fork Face	L2 mm	3290
Performance	4.11	Overall Width	b1/b2 mm	1760/1513
	4.12	Fork Dimensions	s/e/l mm	60x150x1220
	4.13	Fork Carriage to DIN 15173, Class/Form A,B	-	4A
Drive	4.14	Width of Fork Carriage	b3 mm	1524
	4.15	Fork Spread (Out to Out)	s1/s2	330/1510
	4.16	Ground Clearance Mast	m1 mm	150
Others	4.17	Ground Clearance, At Frame	m2 mm	170
	4.18	Aisle Width Pallet 1200x1000 Across Fork	Ast mm	4810
	4.19	Aisle Width Pallet 800x1200 Across Fork	Ast mm	5010
Performance	4.20	Turning Radius	Wa mm	3000
	5.1	Travel Speed, With/Without Load	km/h	18/18
	5.2	Lifting Speed, With/Without Load	m/s	0.5/0.55
Others	5.3	Lowering Speed, With/Without Load	m/s	0.36/0.38
	5.4	Gradability, With/Without Load	%	20/24
	5.5	Service Brake	-	Air Assisted Hydraulic
Drive	5.6	Steering Type	-	Power Steering
	6.1	Engine Manufacturer/ Type	-	Mahindra Mtorque 4745 MCVCN35T1074CE5A
	6.2	Engine/Motor Performance	HP/Kw	74.5/55
Others	6.3	Rated Speed	rpm	2200 (±50 rev/min)
	6.4	Max Torque	Nm@rpm	400 ±5% @1100-1200
	6.5	No. of Cylinders	-	4
Performance	6.6	Fuel Consumption as per VDI Cycle	l/h	NA
	6.7	Battery Voltage/Rated Capacity	v/Ah	12V/130AH
	6.8	Transmission Make/Model	-	CARRARO TLB1 2WD
Others	6.9	Transmission Type	-	Automatic
	6.10	Gear Shift Type	-	SYNCHRO SHUTTLE
Performance	7.1	Transmission Speed	Fwd/Rev	2/2
	7.2	Hydraulic Pump Type	-	Gear Pump
	7.3	Hydraulic Pump Displacement	cc/rev	47.10
Others	7.4	Control Valve Type	-	DC Valve
	7.5	Control Valve Displacement	lpm	80
	7.6	Working Pressure of Hydraulic System	bar	180
Performance	7.7	Hydraulic Oil Tank Capacity	L	80
	7.8	Fuel Tank Capacity	L	75
	7.9	Noise Level at Operators Ear to EN 12053	dB(A)	95dB



DERATION CHART									
Sr. No.	MAST Type	OAH h1 (mm)	FFH h2 (mm)	MFH h3 (mm)	OAH Without LBR h4 (mm)	OAH With LBR h5 (mm)	Tilt FWD/REV a/β	Overhead Guard Height h6 (mm)	Capacity (kg) @MFH
1	HVT STD	2530	NIL	3660	4450	5100	6°/10°	2250	5000
2	HVM	2705	NIL	4000	4800	5450	3°/6°	2250	5000
3	HVM	3070	NIL	4500	5300	5950	3°/6°	2250	4500
4	HVM	3310	NIL	5000	5800	6450	3°/6°	2250	4500
5	HVM	3560	NIL	5500	6300	6950	3°/6°	2250	3800
6	HVT	2100	1300	4200	5000	5650	6°/6°	2150	4250
7	HVT	2400	1600	5100	5900	6550	6°/6°	2250	4000
8	HVT	2900	2100	6500	7250	7900	3°/6°	2250	3500

135+ CUSTOMER TOUCH POINTS FOR SALE AND SERVICE



Stability as per 'BIS'. All specification are subjected to tolerance of ±12% except those governed by BIS. Due to continuous improvements the dimensions are subjected to change without notice. *Dimensions mentioned are for Standard HVM 3600 MFH Model, refer table for other mast configuration.



Address: KION India Private Limited, Gat No. 134/1, Vadhu Road, Off Pune Nagar Road, Koregaon Bhima, Taluka Shirur, District Pune 412216.

Email: in.enquiries@kiongroup.com | Website: www.om-mh.com

TOLL FREE NUMBER- 1800 270 1123