

VL ST VVE 15

1.5 Ton Electric Stacker with capacity of 1500kg @600mm Load Center

Side extraction as Standard



Why Buy Me?

- ✓ Compact design for negotiating narrow aisles
- ✓ Five point wheel configuration with spring suspension for positive traction, grip stability
- ✓ Regenerative braking for power saving
- ✓ Intelligent microprocessor based MOSFET controller of Curtis make
- ✓ Coil protected hydraulics for additional safety and increased performance
- ✓ Anti Roll back on gradient, Side stabilizer, Safety interlock for lifting after FFH, Sturdy platform

Attachments



Technical drawing of the CRP 1000 robot, showing top and side views with dimensions and labels.

Top View Dimensions:

- $b3$, $b5$, e , $b10$, 100 , $b11$, $b1$, $b2$

Side View Dimensions:

- $h4$, $h3$, $h1$, $h2$, $h11$, s , x , y (WHEEL BASE), $l1$, $l4$, $m2$, $h7$, $h12$, $h13$, $h14$

Labels:

- A - BRAKING
- B - TRAVEL
- 600
- C

100+ CUSTOMER TOUCH POINTS FOR SALES & SERVICE

■ KION India
● Dealers
▲ Future locations

Port Blair

100+ CUSTOMER TOUCH POINTS FOR SALES & SERVICE

TUN NORD
100% ISO 9001 / 100% ISO 14001 / 100% ISO 45001
TUN India Private Ltd.

F. MKT: KIPL: 202: 304-00

MAX. FORK LIFT HEIGHT - (h3) mm	HEIGHT OF MAST LOWERED - (CLOSE OAH) - (h1) mm	HEIGHT OF MAST EXTENDED - (OPEN OAH) - (h4) mm	FREE LIFT (h2) mm	CAPACITY AT 600mm L.C. - Kg. (Q)	
				VLST (VVE) 1.5 T WITH SS	VLST (VVE) 1.5 WITHOUT SS
HVT 6500	2800	6930	2300	500	NA
HVT 5400	2450	5870	1920	750	NA
HVT 4500	2150	4970	1640	1000	NA
HVM 3650	2425	4200	NA	NA	1150
HVM 3150	2180	3700	NA	NA	1300
HVM 2750	1990	3300	NA	NA	1500



TOLL FREE NUMBER- 1800 270 1123