

100+ CUSTOMER TOUCH POINTS FOR SALES & SERVICE



F: MKT: KIPL: 302: 352:00

Nov. 2019 - Qty.: 500



Address: KION India Private Limited, Gat No. 134/1, Vadhu Road,
Off Pune Nagar Road, Koregaon Bhima, Taluka Shirur, District Pune 412216.

Email: in.inquiries@kiongroup.com | Website: www.om-mh.com

TOLL FREE NUMBER- 1800 270 1123

100+ YEARS OF GLOBAL TRUST & COMMITMENT



Next Step To Future

XS12 W

1.2 Ton Capacity
Electric Walkie Stacker



WHY BUY ME?

- ✓ Highly specialized drive and hydraulic system ensure excellent driving performance and high reliability.
- ✓ AMP connector and durable electric wires greatly reduce malfunction of components.
- ✓ Safety hydraulic design prevents mast from falling down abruptly when oil pipes cutoff.
- ✓ Ergonomic tiller head for effortless and comfortable operations.
- ✓ Tiller with long arm for smooth steering.
- ✓ Maintenance-free battery
- ✓ Low-voltage cut-off protection
- ✓ Side operating ensures excellent visibility.
- ✓ On- Board Charger.
- ✓ Easy Maintenance – detachable rear panel.
- ✓ Self- Diagnostics signal on the digital display allows easy trouble-shooting.



TOLL FREE NUMBER- 1800 270 1123

BRAND HISTORY

1917




Founded in **1917**; starts in 1918 the production of cars

1933



In **1933**,acquisition by FIAT Group

1937



In **1937** The Plants Of Milan And Brescia Are Unified And The agricultural Machinery Division Of Suzzarals Incorporated With TheGrowth Of 3 New Segments :
1.Buses, Trucks, **2.**Rail Equipment, Agricultural Tractors, Forklift Trucks, Marine Engines
3.Engine Pumps And Cooling Systems

1957



In **1957** OM becomes FIAT Carrelli Elevatori, belonging to IVECO Division

1961



In **1961** PIMESPO, Piccola Industria Meccanica sul Po was born in Luzzara, manufacturing WH Trucks

1981



In **1981** FIAT IVECO acquires PIMESPO.

1992



In **1992** LINDE Group acquires from FIAT the Forklift Division.

2002



In **2002** the Company changes his name into OM Carrelli Elevatori keeping the Brand OM PIMESPO.

2005



In **2005** Luzzara becomes a Plant for the whole STILL Group

2006



In **2006** Linde, Still and OM are unified into the KION Group.

2017



In **2017**, OM launched in Indian market.



OVERALL DIMENSIONS AND SPECIFICATIONS FOR ELECTRIC WALKIE STACKER

1.1	Brand		OM
1.2	Model designation		XS12-W
1.3	Drive unit		Electrical
1.4	Operator type		Pedestrian
1.4	Rated capacity Q	kg	1200
1.5	Load center distance c	mm	600
1.6	Load distance centre of drive axle to fork x	mm	795
1.7	Wheelbase y	mm	1240
1.8	Service weight include battery	kg	661
1.9	Axle loading, laden driving side/loading side	kg	845/1016
1.10	Axle loading, unladen driving side/loading side	kg	536/125
1.11	Tyre type Driving wheels/Loading wheels		PU
1.12	Tyre size, driving wheels diameter×width	mm	210×70
1.13	Tyre size, loading wheels diameter×width	mm	80×60
1.14	Tyre size, caster wheels diameter×width	mm	130×55
1.15	Wheels, number driving caster/loading (x=drive wheels)	mm	1x +1/4
1.16	Track width, front,driving side b ₁₀	mm	533
1.17	Track width,rear,loading side b ₁₁	mm	400
1.18	Height, mast lowered h ₁	mm	2352
1.19	Height mast extended h ₄	mm	4121
1.20	Fork height lowered h ₁₃	mm	88
1.21	Lift height h ₃ +h ₁₃	mm	3615
1.22	Tiller head height in driving position min./max. h	mm	860 / 1200
1.23	Overall length l ₁	mm	1790
1.24	Length to face of forks l ₂	mm	590
1.25	Overall width b ₁ / b ₂	mm	590
1.26	Fork dimensions s / e / l	mm	60 / 170 / 1150
1.27	Fork carriage width b ₃	mm	680
1.28	Distance between fork-arms b ₅	mm	570
1.29	Ground clearance, center of wheelbase m	mm	30
1.30	Aisle width for pallets 1000 × 1200 crossways Ast	mm	2225
1.31	Aisle width for pallets 800 × 1200 lengthways Ast	mm	2150
1.32	Turning radius Wa	mm	1408
1.33	Travel speed, laden/ unladen	km/h	4/4.5
1.34	Lifting speed, laden/ unladen	m/s	0.12 / 0.22
1.35	Lowering speed, laden/ unladen	m/s	0.12 / 0.11
1.36	Max. gradeability, laden/unladen	%	3/10
1.37	Service brake type		Electromagnetic
1.38	Drive motor rating S2 60	min	0.65
1.39	Lift motor rating at S3 15%	kw	2.2
1.40	Battery voltage/nominal capacity K20	V/AH	2x12v / 105AH - GEL
1.41	Type of drive unit		DC
1.42	Steering type		mechanical
1.43	Sound pressure level at the driver's ear dB(A)		74

*The specifications are subject to change without prior notice.

RATED CAPACITIES

Lift Height(mm)	Rated Capacity(kg)
2500	1200
2700	1100
3000	950
3300	800
3600	650

XS12 W

